
 **Important note:** When you edit this page, you agree to release your contribution into the **public domain**. If you don't want this or can't do this because of license restrictions, please don't edit.  This page is one of the *Public Domain Help Pages*, which can be freely copied into fresh wiki installations and/or distributed with Foresight Wiki software; see [Help:Contents](#) for an overview of all pages.

Tables may be authored in wiki pages using either XHTML table elements directly, or using wikicode formatting to define the table. XHTML table elements and their use are well described on various web pages and will not be discussed here. The benefit of wikicode is that the table is constructed of character symbols which tend to make it easier to perceive the table structure in the article editing view compared to XHTML table elements.

As a general rule, it is best to avoid using a table unless you need one. Table markup often complicates page editing.

Contents

- [1 Wiki table markup summary](#)
- [2 Basics](#)
 - ◆ [2.1 Table headers](#)
 - ◆ [2.2 Caption](#)
- [3 XHTML attributes](#)
 - ◆ [3.1 Attributes on tables](#)
 - ◆ [3.2 Attributes on cells](#)
 - ◆ [3.3 Attributes on rows](#)
 - ◆ [3.4 With HTML attributes and CSS styles](#)
- [4 Caveats](#)
 - ◆ [4.1 Negative numbers](#)
 - ◆ [4.2 CSS vs Attributes](#)

Wiki table markup summary

{	table start
+	table caption , <i>optional</i> ; only between table start and first table row
-	table row , <i>optional on first row</i> -- wiki engine assumes the first row
!	table header cell, <i>optional</i> . Consecutive table header cells may be added on same line separated by double marks (! !) or start on new lines, each with its own single mark (!).
	table data cell, <i>required!</i> Consecutive table data cells may be added on same line separated by double marks () or start on new lines, each with its own single mark ().
}	table end

Help:Tables

- The above marks must **start on a new line** except the double `| |` and `! !` for optionally adding consecutive cells to a line. However, blank spaces at the beginning of a line are ignored.
- **XHTML attributes.** Each mark, except table end, optionally accepts one or more XHTML attributes. Attributes must be on the same line as the mark. Separate attributes from each other with a single space.
 - ◆ Cells and caption (`|` or `| |`, `!` or `! !`, and `| +`) hold content. So separate any attributes from content with a single pipe (`|`). Cell content may follow on same line or on following lines.
 - ◆ Table and row marks (`{ |` and `| -`) do not directly hold content. Do *not* add pipe (`|`) after their optional attributes. If you erroneously add a pipe after attributes for the table mark or row mark the parser will delete it *and* your final attribute if it was touching the erroneous pipe!
- **Content** may (a) follow its cell mark on the same line after any optional XHTML attributes or (b) on lines below the cell mark. Content that uses wiki markup that itself needs to start on a new line, such as lists, headings, or nested tables, must be on its own new line.
- **Escaping** to insert a pipe (`|`) character into a table use the `<nowiki>` markup

Basics

The following table lacks borders and good spacing but shows the simplest wiki markup table structure.

You type	You get
<pre>{ Orange Apple - Bread Pie - Butter Ice cream }</pre>	<pre>Orange Apple Bread Pie Butter Ice cream</pre>

The cells in the same row can be listed on one line separated by `| |`.

Extra spaces within cells in the wiki markup, as in the wiki markup below, do not affect the actual table rendering.

You type	You get
<pre>{ Orange Apple more - Bread Pie more - Butter Ice cream and more }</pre>	<pre>Orange Apple more Bread Pie more Butter Ice cream and more</pre>

Table headers

Table headers can be created by using `!"` instead of `"|"`. Headers usually show up bold and centered by default.

You type	You get
----------	---------

{	
! Item	
! Amount	
! Cost	
-	
Orange	
10	
7.00	Item Amount Cost
-	
Bread	Orange 10 7.00
4	Bread 4 3.00
3.00	Butter 1 5.00
-	
Butter	Total 15.00
1	
5.00	
-	
!Total	
15.00	
}	

Caption

A **table caption** can be added to the top of any table as follows.

You type	You get
{	
+Food complements	Food complements
-	
Orange	
Apple	
-	Orange Apple
Bread	Bread Pie
Pie	
-	Butter Ice cream
Butter	
Ice cream	
}	

XHTML attributes

You can add XHTML attributes to tables. For the authoritative source on these, see [the W3C's HTML 4.01 Specification page on tables](#).

Attributes on tables

Placing attributes after the table start tag (`{|`) applies attributes to the entire table.

You type	You get		
{ border="1"	Orange	Apple	12,333.00
Orange	Bread	Pie	500.00
Apple	Butter		1.00
12,333.00			
-			

Table headers

Bread			
Pie		Ice cream	
500.00			
-			
Butter			
Ice cream			
1.00			
}			

Attributes on cells

You can put attributes on individual **cells**. For example, numbers may look better aligned right.

You type	You get		
{ border="1"			
Orange			
Apple			
align="right" 12,333.00	Orange	Apple	12,333.00
-	Bread	Pie	500.00
Bread	Butter	Ice cream	1.00
Pie			
align="right" 500.00			
-			
Butter			
Ice cream			
align="right" 1.00			
}			

You can also use **cell** attributes when you are listing multiple **cells** on a single line. Note that the **cells** are separated by ||, and within each **cell** the attribute(s) and value are separated by |.

You type	You get		
{ border="1"			
Orange Apple align="right" 12,333.00	Orange	Apple	12,333.00
-	Bread	Pie	500.00
Bread Pie align="right" 500.00	Butter	Ice cream	1.00
-			
Butter Ice cream align="right" 1.00			
}			

Attributes on rows

You can put attributes on individual **rows**, too.

You type	You get		
{ border="1"	Orange	Apple	12,333.00
Orange	Bread	Pie	500.00
Apple	Butter	Ice cream	1.00
align="right" 12,333.00			
-			
Bread			
Pie			
align="right" 500.00			
- style="font-style:italic; color:green;"			
Butter			
Ice cream			
align="right" 1.00			

Attributes on tables

```
|}
```

With HTML attributes and CSS styles

CSS style attributes can be added with or without other HTML attributes.

You type				
<pre>{ style="color:green; background-color:#ffffcc;" cellpadding="20" cellspacing="0" border="1" Orange Apple - Bread Pie - Butter Ice cream }</pre>	<table border="1"> <tr> <td>Orange</td> </tr> <tr> <td>Bread</td> </tr> <tr> <td>Butter</td> </tr> </table>	Orange	Bread	Butter
Orange				
Bread				
Butter				

Attributes can be added to the caption and headers as follows.

You type	You get	
<pre>{ border="1" cellpadding="20" cellspacing="0" + align="bottom" style="color:#e76700;" 'Food complements'' - Orange Apple - Bread Pie - Butter Ice cream }</pre>	Orange	Apple
	Bread	Pie
	Butter	Ice cream
	<i>Food complements</i>	

Caveats

Negative numbers

If you start a cell on a new line with a negative number with a minus sign (or a parameter that evaluates to a negative number), your table can get broken, because the characters `| -` will be parsed as the wiki markup for table row, not table cell. To avoid this, insert a space before the value (`| -6`) or use in-line cell markup (`| | -6`).

CSS vs Attributes

Table borders specified through CSS rather than the border attribute will render incorrectly in a small subset of text browsers.